



Hi-Brite

7015TXO 750W GX9.5 100V 1CT/10

The compact, shock-resistant design of the Hi-Brite lamp series makes it easy to handle and ideal for moving head systems. Also, the compact filament ensures a high beam intensity, which can be used to reduce energy consumption: for example, 1200W can now be used instead of 2500W. In addition, the highly innovative P3 technology, developed by Philips, allows the lamp to be used at higher temperatures in any burning position, which further extends lamp lifetime, reduces lamp replacement costs and ensures consistency of high-quality light output.


Product data

| General Information | |
|------------------------------------|-----------------------------------|
| Cap-Base | GX9.5 [GX9.5] |
| Philips Code | 7015TXO |
| ANSI Code | - |
| Operating Position | UNIVERSAL [Any or Universal (U)] |
| Main Application | Entertainment |
| Life to 50% Failures (Nom) | 300 h |
| System Description | P3 Technology |
| Light Technical | |
| Luminous Flux (Rated) (Nom) | 20250 lm |
| Correlated Color Temperature (Nom) | 3200 K |
| Color Rendering Index (Nom) | - |
| Operating and Electrical | |
| Power (Rated) (Nom) | 750 W |
| Voltage (Nom) | 100 V |
| Controls and Dimming | |
| Dimmable | Yes |

| Mechanical and Housing | |
|---------------------------------|--------------------------------|
| Bulb Finish | Clear |
| Filament Shape | Bi-Plane |
| Filament Dimensions WxH | - |
| Luminaire Design Requirements | |
| Pinch Temperature (Max) | 500 °C |
| Product Data | |
| Full product code | 871150050557625 |
| Order product name | 7015TXO 750W GX9.5 100V 1CT/10 |
| EAN/UPC - Product | 8711500505576 |
| Order code | 924574530928 |
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 10 |
| Material Nr. (12NC) | 924574530928 |
| Net Weight (Piece) | 0.037 kg |

Hi-Brite

Dimensional drawing



| Product | D (max) | H | W | L | C (max) |
|--------------------------------|---------|--------|--------|-------|---------|
| 7015TXO 750W GX9.5 100V 1CT/10 | 19 mm | 8.5 mm | 9.5 mm | 55 mm | 104 mm |

7015TXO 750W GX9.5 100V

