



# Halogen non-reflector

## 7724I 100W GY6.35 12V 1CT/10X10F

Halogen non-reflector lamps offer high-quality light and are easy to install, replace and operate. All halogen non-reflector lamps incorporate a distortion-free quartz bulb and a precise positioning of the mounted filament. These ensure optimal beam performance and consistent, high light output. A wide range of wattages is available for a broad variety of applications, including projection systems. In addition you get all the proven advantages of halogen technology such as a full spectrum and a color rendering index (CRI) of 100 – the same as natural light and the best that it can be. Halogen lamps also create a comfortable warm white light, and they maintain their lumen output, with almost no reduction, throughout their lifetime.


### Product data

General Information	
Cap-Base	GY6.35 [ GY6.35]
Philips Code	7724I
ANSI Code	EVA
LIF Code	-
Operating Position	S90 [ Standing +/-90D or Base Down (BDH)]
Main Application	Projection
Life to 50% Failures (Nom)	2000 h
Light Technical	
Luminous Flux (Rated) (Nom)	2800 lm
Correlated Color Temperature (Nom)	3300 K
Color Rendering Index (Nom)	100
Operating and Electrical	
Power (Nom)	100 W
Voltage (Nom)	12 V

Mechanical and Housing	
Bulb Material	Quartz-UV Open
Filament Shape	Flat
Filament Dimensions WxH	4.82x3.0
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C
Pinch Temperature (Max)	350 °C
Product Data	
Full product code	871150041280550
Order product name	7724I 100W GY6.35 12V 1CT/10X10F
EAN/UPC - Product	8711500412805
Order code	923875717103
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	100
Material Nr. (12NC)	923875717103
Net Weight (Piece)	0.002 kg

## Halogen non-reflector

### Dimensional drawing



7724I 100W GY6.35 12V

#### Product

7724I 100W GY6.35 12V 1CT/10X10F

