



MSR

MSR 1200 1CT/3

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Warnings and Safety


- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Operating Position	UNIVERSAL [Any or Universal (U)]
Cap-Base	G22 [G22]
Light Technical	
Color Code	- [Not Specified]
Luminous Flux	103,000 lumen
Chromaticity Coordinate X (Nom)	325
Chromaticity Coordinate Y (Nom)	327
Correlated Color Temperature (Nom)	5900 K
Luminous Efficacy (rated) (Nom)	88 lm/W
Color rendering index (CRI)	80
Operating and Electrical	
Power Consumption	1,200 W


Lamp Current (Nom)	13.8 A
Controls and Dimming	
Dimmable	No
Product Data	
Full product code	872790091121300
Order product name	MSR 1200 1CT/3
Order code	928078105114
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	3
Material number (12NC)	928078105114
Full product name	MSR 1200 1CT/3
EAN/UPC - Case	8727900911220

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 1200 1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm

Photometric data



Spectral Power Distribution Colour - MSR 1200 1CT/3

