



# **Halogen reflector**

## 14527 150W GX5.3 21V 1CT

Quartz halogen lamps with integral reflector which serves as an efficient mirror condenser system

#### **Product data**

General Information	
Cap base	GX5.3 [ GX5.3]
Philips code	14527
ANSI Code	EJA
LIF code	-
Burning Position	S90 [ Standing +/-90D or Base Down (BDH)]
Main application	Projection
Life to 50% failures (nom.)	40 h
Light Technical	
Colour Temperature, horizontal (Nom)	3400 K
Colour Rendering Index,horiz (Nom)	100
Operating and Electrical	
Power (Rated) (Nom)	150 W
Voltage (Nom)	21 V
Controls and Dimming	
Dimmable	yes
Mechanical and Housing	
Bulb material	Quartz-UV Open


Filament snape	
Filament dimensions WxH	-
Luminaire Design Requirements	
Bulb temperature (max.)	900 °C
Pinch temperature (max.)	400 °C
Working distance WD	28 mm
Product Data	
Full product code	871150041256030
Order product name	14527 150W GX5.3 21V 1CT
EAN/UPC - product	8711500412560
Order code	924041119894
Numerator – quantity per pack	1
Numerator – packs per outer box	24
Material no. (12NC)	924041119894
Net weight (piece)	0.024 kg

Datasheet, 2019, September 3 data subject to change

Reflector finish

# Halogen reflector

### Dimensional drawing



Product	D (max)	C (max)
14527 150W GX5.3 21V 1CT	50.7 mm	44.5 mm



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.